Brammer Standard Company, Inc.

Certificate of Analysis

B.S. 51E AISI 4615 Grade Low Alloy Steel

Carbon	0.15	Aluminum	0.028
Manganese	0.59	Cobalt	0.035
Phosphorus	0.010	Nitrogen	0.0086
Sulfur	0.021	Oxygen	(0.004)
Silicon	0.28	Tin	0.010
Copper	0.22	Vanadium	(0.0011)
Nickel	1.75		
Chromium	0.14		
Molybdenum	0.21		

(analysis listed as percent by weight)

Some of the co-operating laboratories were:

Allegheny Ludlum Steel Corp., Brackenridge, Pennsylvania Brammer Standard Co., Inc., Houston, Texas Charles C. Kawin Company, Maywood, Illinois Chicago Spector Service Laboratory, Chicago, Illinois Crobaugh Laboratories, Cleveland, Ohio Crucible Specialty Metals, Syracuse, New York J. Dirats and Co., Inc., Westfield, Massachusetts Jessop Steel Company, Washington, Pennsylvania Midstates Analytical Laboratories, Inc., Tulsa, Oklahoma VHG Laboratories, Inc., Manchester, New Hampshire

See reverse side for more information.

Certificate Number REV51E-032092

Analysis	C	Mn	P	S	Si	Cu	Ni	Cr	Mo
1 2 3 4 5 6 7	0.14 0.143 0.145 0.147 0.15 0.16	0.58 0.58 0.58 0.59 0.59 0.59 0.60	0.008 0.009 0.011 0.011 0.011 0.012	0.019 0.020 0.020 0.022 0.0227 0.023 0.023	0.28 0.28 0.28 0.29 0.29 0.29	0.207 0.21 0.215 0.218 0.22 0.22	1.73 1.74 1.74 1.74 1.75 1.76 1.77	0.134 0.137 0.14 0.14 0.14 0.147 0.15	0.205 0.206 0.209 0.210 0.21 0.21 0.21
Average	0.148	0.590	0.0103	0.0214	0.285	0.216	1.751	0.141	0.210
Std Dev	0.007	0.009	0.0015	0.0017	0.005	0.006	0.017	0.006	0.005
Certified	0.15	0.59	0.010	0.021	0.28	0.22	1.75	0.14	0.21

Analysis	Al	Со	N	0	Sn	V
1 2 3 4 5 6 7	0.026 0.0262 0.028 0.028 0.028 0.028 0.029 0.0309 0.031	0.033 0.0336 0.0349 0.037	0.0084 0.0086 0.0089	0.0036	0.0088 0.009 0.009 0.0099 0.010 0.0106 0.011	0.0009 0.0012
Average	0.0284	0.0346	0.0086		0.0099	0.0011
Std Dev	0.0019	0.0018	0.0003		0.0009	0.0002
Certified	0.028	0.035	0.0086	(0.004)	0.010	(0.0011)

Data in parentheses are not certified but provided for information only.

Chemical analyses were made on millings from cross-sections of the bars. The individual values listed above are the average of each analyst's results.

Methods of analysis used were a combination of ASTM Standard Methods E 350, E 415, E 1019, plus additional ICP, and AA spectrometric methods. The following Certified Reference Materials were used to validate the analytical data listed above: NIST SRM 32e, 125b, 361 to 365; BAM 039-2, 044-1; BCS 455/1, 456/1, 458/1; ECRM 085-1, 088-1, 096-1, 184-1, 481-1; GBW 01402; IMZ 1.22, 1.74

This Reference Material was tested for homogeneity using ASTM Standard Method E 826 and found acceptable. It was also examined by optical emission spectrometry and found to be compatible with the following NIST Certified Reference Materials: SRM 1222, 1224, 1225, 1261A to 1265A, 1761 to 1767

The bar stock used for this material was produced by hot-rolling billets and annealing. The entire depth of the disc may be used.

A Material Safety Data Sheet (MSDS) is not required for this material. This material will not release or otherwise result in exposure to a hazardous chemical, under normal conditions of use. Inquiries concerning this Reference Material should be directed to:

Brammer Standard Co., Inc. Phone: (281) 440-9396 14603 Benfer Road Houston, Texas 77069-2895 USA Fax: (281) 440-4432

Certified by: _____ on March 20, 1992.

This is a revision of the original certificate of analysis. The material was retested by additional laboratories in 1991 and 1992. Additional elements are now certified. Also, as a result of the retesting, the certified analysis has been revised slightly for sulfur, copper, nickel, vanadium, and aluminum.