

BRAMMER STANDARD COMPANY, INC.

Certificate of Analysis

BS H1C

Certified Reference Material for Hastelloy type B-2 - UNS Number N10665

	Certified Value ¹	Estimate of Uncertainty ²	Certified Values ³	Certified Value ¹	Estimate of Uncertainty ²
Al	0.15	0.01		Mn	0.01
C	0.0022	0.0004		Mo	0.3
Cr	0.70	0.02		Ni	0.2
Fe	1.29	0.02			

	Reference Value ¹	Estimate of Uncertainty ²	Reference Values ^{3,4}	Reference Value ¹	Estimate of Uncertainty ²
P	0.0049	0.0003			

Informational Values^{3,5}

As (0.001)	B (0.001)	Ca (0.001)	Co (0.01)	Cu (0.002)
Mg (0.0012)	N (0.0005)	Nb (0.009)	O (0.0009)	Pb (0.00002)
S (0.0004)	Si (0.01)	Sn (0.002)	Ta (0.009)	Ti (0.008)
V (0.02)	W (0.009)	Zr (0.001)		

¹ For each element, the certified value listed is the present best estimate of the true value based on the mean of the weighted results of an interlaboratory testing program. See page 4 for more information on its calculation.

² For each element, the uncertainty listed is based on a statistical evaluation of the contributions of homogeneity and the interlaboratory testing program. See page 4 for more information on its calculation.

³ Values are given in weight percent. Values in brackets are reported by difference.

⁴ Reference values are not certified and are provided for information only.

⁵ Values in parentheses are not certified and are provided for information only.

Trace element information values for Ba, Nd, Se, Te, and Zn are shown on page 4.

The requirements of ISO Guides 31, 34, and 35 were followed for the preparation of this Certified Reference Material and certificate of analysis. This is a Certified Reference Material as defined by ISO Guide 30.

BS H1C

* Code for method Certified values listed as weight percent

Brammer Standard Company, Inc., 14603 Benfer Road, Houston, TX 77069-2895

Telephone: (281) 440-9396 Fax: (281) 440-4432 Website: www.brammerstandard.com

Certificate Number H1C-101016 Page 1/7

Analysis	*	Al	*	C	*	Cr	*	Fe	*	Mn	*	Mo	*	Ni
1	14	0.131667	1	0.0009	10	0.606667	10	1.236667	3	0.458	4	26.7	16	[69.10333]
2	4	0.131833	1	0.001667	4	0.670667	4	1.259	4	0.484667	4	26.72	10	69.301
3	3	0.132	1	0.001833	13	0.679	3	1.26	4	0.494333	4	26.833	3	69.33667
4	5	0.1400	1	0.002133	4	0.683333	3	1.27	4	0.494333	10	26.99667	10	69.60
5	10	0.15	1	0.002367	4	0.692333	4	1.276667	8	0.496	3	27.19	13	69.63967
6	3	0.150333	1	0.002467	10	0.694	14	1.2800	3	0.50	4	27.2108	16	[69.64]
7	12	0.153333	1	0.002467	10	0.70	4	1.28	10	0.508	14	27.23333	4	69.72
8	4	0.154667	1	0.002523	4	0.703333	4	1.280333	3	0.508433	10	27.38	4	69.75333
9	4	0.156667	1	0.002833	10	0.713333	4	1.292	4	0.51	3	27.425	14	69.76667
10	4	0.160333	3	0.002867	4	0.721633	4	1.296667	10	0.513	4	27.50	3	69.84797
11	4	0.164667			3	0.7256	10	1.296667	4	0.514	4	27.54333	10	69.87
12	5	0.167333			3	0.754667	3	1.2987	10	0.516	10	27.56	16	[69.9283]
13	3	0.17			4	0.773667	10	1.30	4	0.517167	3	27.61667	10	70.22667
14	10	0.171333					12	1.3000	14	0.521	4	27.63333	16	[70.49667]
15	4	0.194333					4	1.318333	4	0.523267			4	70.56333
16							4	1.33	4	0.529			4	70.73333
17							4	1.34	4	0.53				
18									10	0.533333				
19									3	0.535				
Average		0.1530		0.00221		0.7093		1.289120		0.5106		27.22		69.840
Std dev		0.0033		0.00010		0.0089		0.000077		0.0047		0.10		0.048
H		0.0030		0.00042		0.008		0.012		0.0064		0.15		0.38
U ₁		0.0044		0.00043		0.012		0.012		0.0080		0.19		0.38
t-statistic		2.14		2.26		2.18		2.12		2.10		2.16		2.13
U ₂		0.010		0.0010		0.026		0.026		0.017		0.40		0.81
U ₃		0.0025		0.00031		0.0073		0.0063		0.0038		0.11		0.20
Certified		0.15		0.0022		0.70		1.29		0.51		27.2		69.8
Uncertainty		0.01		0.0004		0.02		0.02		0.01		0.3		0.2
Tolerance		0.03		0.0010		0.06		0.06		0.03		0.9		0.8

BS H1C * Code for method Reference values listed as weight percent

Analysis	*	P
1	12	0.0021333
2	5	0.0034667
3	4	0.00351
4	5	0.00384
5	10	0.0043
6	3	0.0046667
7	3	0.0052
8	4	0.0052
9	4	0.0053333
10	4	0.0057
11	14	0.0059333
12	5	0.0061
13	4	0.0063
14	10	0.0064333
Average		0.004865
Std dev		0.000085
H		0.00055
U ₁		0.00056
t-statistic		2.16
U ₂		0.0012
U ₃		0.00032
Reference		0.0049
Uncertainty		0.0003
Tolerance		0.0012

BS H1C * Code for method Informational values listed as weight percent

Analysis	*	As	*	B	*	Ca	*	Co	*	Cu	*	Mg	*	N	*	Nb
1	12	0.000006	12	0.000507	12	0.000017	12	0.0067	12	0.0003	4	0.00083	2	0.000117	12	0.0000533
2	5	0.0024	4	0.0006	3	0.00054	4	0.007103	5	0.0005567	5	0.001133	2	0.000133	5	0.0000967
3			7	0.000607	4	0.000767	4	0.0074	5	0.0015	5	0.0012	2	0.000493	5	0.0001
4			4	0.0010	4	0.0043	5	0.0075	10	0.0022	5	0.001233	2	0.0005	4	0.0016667
5			4	0.001167	4	0.0081	3	0.0028667	12	0.0014	2	0.000513	4	0.002		
6			3	0.001233	5	0.0089	3	0.003	14	0.001567	2	0.000688	4	0.0053333		
7			3	0.00205	3	0.008933	14	0.0031	2	0.000767	14	0.0136667				
8			3	0.0021	5	0.0091	4	0.0058667	2	0.0009	3	0.0262				
9			14	0.0024	4	0.013333	10	0.020	10	0.031						
10			4	0.002767	10	0.020	14	0.0228	4	0.023033						
11					14	0.0228	4	0.0241	4	0.0241						
12					4	0.023033	3	0.0353	3	0.0353						
13																
14																
Average		0.0012		0.0014		0.0014		0.014		0.002		0.0012		0.00051		0.009
Std dev		0.0072		0.0044		0.0067		0.091		0.011		0.0043		0.00073		0.065
H		0.0003		0.0004		0.0004		0.001		0.0004		0.0003		0.00027		0.001
U ₁		0.0072		0.0044		0.0067		0.091		0.012		0.0043		0.00078		0.065
t-statistic		12.71		2.26		3.18		2.16		2.36		2.57		2.36		2.31
U ₂		0.092		0.010		0.021		0.20		0.027		0.011		0.0019		0.15
U ₃		0.065		0.0032		0.011		0.053		0.0096		0.0045		0.00066		0.050
(Informational)		(0.001)		(0.001)		(0.001)		(0.01)		(0.002)		(0.0012)		(0.0005)		(0.009)

Analysis	*	O	*	Pb	*	S	*	Si	*	Sn	*	Ta	*	Ti	*	V
1	1	0.00037	12	0.000017	12	0.000068	5	0.0046	4	0.001833	4	0.005267	4	0.0005	12	0.000049
2	1	0.000511			1	0.0001	12	0.0065	3	0.0121	5	0.000687	4	0.0002		
3	1	0.000533			1	0.000207	4	0.007	12	0.000703	4	0.001433				
4	1	0.00055			1	0.000233	5	0.0077	5	0.0050	3	0.0051				
5	1	0.000563			1	0.0004	4	0.009533	4	0.0055	14	0.005467				
6	1	0.000633			1	0.000467	4	0.012033	4	0.013633	4	0.0071				
7	1	0.000867			1	0.000567	4	0.016333	3	0.015	4	0.023333				
8	1	0.0015			3	0.0013	3	0.017067	4	0.015033	3	0.0881				
9	1	0.002333					14	0.0249	14	0.0157						
10							4	0.025167								
11							3	0.0254								
Average		0.0009		0.00001700		0.00042		0.01		0.002		0.01		0.01		0.02
Std dev		0.0019		0.00000056		0.00048		0.10		0.021		0.13		0.11		0.14
H		0.0003		0.000175		0.0003		0.0007		0.0004		0.0007		0.0007		0.001008
U ₁		0.0019		0.00018		0.00055		0.10		0.021		0.13		0.11		0.14
t-statistic		2.31		12.71		2.36		2.23		12.71		12.71		2.31		2.36
U ₂		0.0045		0.0022		0.0013		0.22		0.26		1.71		0.26		0.32
U ₃		0.0015		0.0022		0.00046		0.068		0.26		1.21		0.088		0.11
(Informational)		(0.0009)		(0.00002)		(0.0004)		(0.01)		(0.002)		(0.009)		(0.008)		(0.02)

BS H1C * Code for method Informational values listed as weight percent

Analysis	*	W	*	Zr
1	5	0.004867	12	0.000020
2	5	0.005167	4	0.001
3	12	0.005633	4	0.0011
4	4	0.006533	10	0.0013
5	4	0.0075	3	0.0015
6	4	0.01		
7	3	0.0137		
8	4	0.014067		
9	4	0.015067		
Average		0.009		0.0010
Std dev		0.068		0.0032
H		0.0007		0.000327
U ₁		0.068		0.0032
t-statistic		2.31		2.78
U ₂		0.16		0.0089
U ₃		0.052		0.0040
(Informational)		(0.009)		(0.001)

For each element, in accordance with the requirements of ISO Guides 34 and 35, an effort must be made to account for the effects on the certified value of the uncertainty estimate from homogeneity testing (H) and the uncertainties of the contributing laboratories. The average (A) is calculated using a weighted mean where the reciprocal of the square of each laboratory's combined uncertainty (C_L), calculated from its standard deviation (S_L) and its uncertainty estimate (U_L), is used as the weight (W_L) for its mean (M_L). The standard deviation (S) is calculated as the square root of the reciprocal of the sum of the weights. U₁ is the combined uncertainty from homogeneity and labs. U₂ is U₁ multiplied by the coverage factor (95 % t-statistic). U₃ is U₂ divided by the square root of the number of determinations (n). Thus:

$$C_L = \sqrt{S_L^2 + U_L^2} \quad W_L = \frac{1}{C_L^2} \quad A = \frac{\sum_{i=1}^n W_L M_L}{\sum_{i=1}^n W_L} \quad S = \frac{1}{\sqrt{\sum_{i=1}^n W_L}} \quad U_1 = \sqrt{H^2 + S^2} \quad U_2 = t \times U_1 \quad U_3 = \frac{U_2}{\sqrt{n}}$$

All but the final reported values are taken to two significant figures as determined by each quantity's uncertainty estimate. The final reported Uncertainty is U₃ rounded to one significant figure and represents the half width of the 95 % confidence interval for the **Certified** value. The final reported **Certified** value is A rounded to the same decimal place as the Uncertainty. The Uncertainty is a measure of the quality of the **Certified** value.

The Tolerance is a measure of the expected performance of an analysis. This involves further expanding the sample uncertainty to include instrument and operator uncertainty, for those without access to such calculations.

For further information regarding the confidence interval for the certified value see ISO Guide 35:2006 section 6.

BS H1C * Code for analytical method Trace analysis listed as mg/kg (ppm)

Analysis	*	Ba	*	Nd	*	Se	*	Te	*	Zn
1	5	2	5	5	5	3	5	13	12	1.2

Analytical Method Codes:

1 Combustion (ASTM E1019)	7 Photometric	13 Titrimetric
2 Fusion (ASTM E1019)	8 Flame Atomic Absorption	14 DCP Atomic Emission
3 Spark Atomic Emission	9 GF Atomic Absorption	15 HG Atomic Fluorescence
4 ICP Atomic Emission	10 X-Ray Fluorescence	16 Difference
5 ICP Mass Spectrometry	11 GD Atomic Emission	
6 Gravimetric	12 GD Mass Spectrometry	

ICP = Inductively Coupled Plasma GF = Graphite Furnace GD = Glow Discharge
 DCP = Direct Current Plasma HG = Hydride Generation

<u>Laboratory</u>	<u>Location</u>	<u>Registrar</u>	<u>Accreditation</u>
Brammer Standard Company, Inc.	Houston, TX	A2LA	17025, Guide 34
Evans Analytical Group	Liverpool, NY	A2LA	17025
NSL Analytical	Cleveland, OH	ACCLASS	17025
Dirats Laboratories	Westfield, MA	ACCLASS	17025
Anderson Laboratories, Inc.	Greendale, WI	A2LA	17025
Instytut Metalurgii Zelaza	Gliwice, Poland	PCA	AB 554
Elemental Analysis, Inc.	Lexington, KY	A2LA	17025
Evans Analytical Group	Liverpool, NY	A2LA	17025
Exova	Glendale Heights, IL	A2LA	17025
National Analysis Center For Iron And Steel	Beijing, China	CNAS	17025
Luvak Inc.	Boylston, MA	PRI/Nadcap	17025

A2LA = American Association for Laboratory Accreditation

ACCLASS = ANSI-ASQ National Accreditation Board

CNAS = China National Accreditation Service

Nadcap = National Aerospace and Defense Contractors Accreditation Program

PCA = Polish Center For Accreditation

PRI = Performance Review Institute

Analysis: Chemical analyses were made on solid pieces and chips prepared by an end mill from representative samples for the certified portion of the lot in accordance with ASTM Standard Practice E1806. The laboratories participating in the testing followed the requirements of ISO Standard 17025.

Traceability: The following Certified Reference Materials were used to validate the analytical data: 13X32101A, 212X4003, 212X4003K, 212X4004, 212X4004K, 215XHB2F, 215XHB5K, 24X07001; LECO 501-501, 501-550, 501-566, 501-591, 501-644, 501-645, 501-646, 501-675, 501-676, 501-991, 501-992, 501-993, 502-348, 502-873; AR 645, 654, 673, 875, 892, 946, 1648, 1652, 1653; BAS 349, 351, 387, 451; BS H1, H1A, H1B, H2A, H2C, H2D, H6B, 200, 200-1, 200-2, 200-3, 400D, 750C; DSZU CA01A; IARM 16, 52A, 54B, 56C, 63A, 63C, 257A; IMZ 184; JSS GS-6; KMS LSCON-001; NCS NS11028; SRM 160B, 166C, 349, 349A, 865, 866, 867, 882, 1413, 3109A, 3114, 3150.

Homogeneity: This Certified Reference Material (CRM) was tested for homogeneity using ASTM Standard Method E826 and found acceptable. It was also examined by spark atomic emission spectrometry and found to be compatible with the following Reference Materials — LECO 501-676, 502-873; BAS 351; BS H2, H1A, H1B, H2A, H2C, H2D, 200; DSZU CA01A; KMS LSCON-001; NCS NS11028; SRM 106B, 882.

Validity statement: ISO Guide 31 states that the certification should contain an expiration date for all materials where instability has been demonstrated or is considered possible, after which the certified value is no longer guaranteed by the certifying body. The certification of BS H1C is valid indefinitely. The certification is nullified if this CRM is damaged, contaminated, or otherwise modified.

Source: The bar stock for this CRM was produced by VDM Metals USA, LLC; Reno, NV.

Form: This CRM is machined in the form of a disc, approximately 38 mm in diameter and 19 mm thick by Brammer Standard Company, Inc.

Use: This CRM is intended for use in spark atomic emission, glow discharge, and x-ray spectrometric methods of analysis. Refer to

Brammer Standard Company, Inc., 14603 Benfer Road, Houston, TX 77069-2895
Telephone: (281) 440-9396 Fax: (281) 440-4432 Website: www.brammerstandard.com
 Certificate Number H1C-101016 Page 5/7

ISO Guide 33 for information about the use of Certified Reference Materials.

Certified Area: The entire depth of the CRM may be used.

Caution: As with any bar material, avoid spark atomic emission spectrometric burns in the center of the CRM (5 mm radius), as some segregation may be present.

Sample Preparation: For best analytical results, use the same method for preparing the analytical surface on all reference materials as used for production specimens. Avoid overheating the sample during surface preparation.

Certificate Number: The unique identification number for this certificate of analysis is H1C-101016. You may obtain information on revisions of certificates from the internet at www.brammerstandard.com.

Safety Notice: A Safety Data Sheet (SDS) is not required for this material. This material will not release or otherwise result in exposure to a hazardous chemical, under normal conditions of use. Inquiries concerning this Reference Material should be directed to:

Brammer Standard Co., Inc. **Phone: (281) 440-9396** **Web: www.brammerstandard.com**
14603 Benfer Road
Houston, Texas 77069-2895 USA **Fax: (281) 440-4432** **Email: contact@brammerstandard.com**

Brammer Standard Company, Inc., is accredited by the American Association For Laboratory Accreditation (A2LA) to ISO Guide 34 as a Reference Material Producer for the production of Certified Reference Materials and Reference Materials (Certificate Number 656.02)

Brammer Standard Company's Chemical Laboratory is accredited by A2LA to ISO Standard 17025. (Certificate Number 656.01)

By Certificate Number 10539, the Quality System of Brammer Standard Company, Inc., is registered to ISO 9001:2008 by National Quality Assurance (NQA), U.S.A.

The scopes of accreditation are listed on the website: www.brammerstandard.com

References:

Versions used were those available at the time of testing and characterization

- | | |
|-------|---|
| E826 | Standard Practice for Testing Homogeneity of a Metal Lot or Batch in Solid Form by Spark Atomic Emission Spectrometry |
| E1019 | Standard Test Methods for Determination of Carbon, Sulfur, Nitrogen, and Oxygen in Steel, Iron, Nickel, and Cobalt Alloys by Various Combustion and Fusion Techniques |
| E1806 | Standard Practice for Sampling Steel and Iron for Determination of Chemical Composition |

ISO Standard 17025:2005 General requirements for the competence of testing and calibration laboratories

ISO Standard 9001:2008 Quality Management Systems - Requirements

ISO Guide 30:2015 Terms and definitions used in connection with reference materials + 2008 amendment

ISO Guide 31:2015 Reference materials - Contents of certificates and labels

ISO Guide 33:2015 Uses of certified reference materials

ISO Guide 34:2009 General requirements for the competence of reference material producers

ISO Guide 35:2006 Reference Materials - General and statistical principles for certification

ASTM documents available from ASTM, 100 Barr Harbor Dr., West Conshohocken, Pa 19428.

ISO Guides and Standards available from Global Engineering - www.global.ihs.com

Other useful documents available from NIST, U.S. Department of Commerce, Gaithersburg, MD 20899.

NIST Special Publication 260-100, Handbook for SRM Users

NIST Special Publication 829, Use of NIST Standard Reference Materials for Decisions on Performance of Analytical Chemical Methods and Laboratories

Certified by: _____ on October 10, 2016.

Beau R. Brammer